



Shenzhen OKD Technology Co.,Ltd

OKD-DB20



Name	OKD-DB20
Product Features	The built-in copper baffle activities before and after, and the baffle with dry reed pipe magnet switch signals are given
Material	Copper, inside the tooth interface, the structure is simple, practical, and can have a one-way valve role
LWH(MM)	56*32*75
ID	G3/4"
startup flow rate	7L/min
maximum stream flow	20L/min
Startup flow power	70W
operating pressure	0.005-1.0Mpa
Max pressure	1.5Mpa
Media	WATER
Operating temperature	≤80℃
Installation Method	With products for water into the direction of arrow, level installation
flow control	Start flow can fine-tune, loosen switch fixed nut, up-down adjustment with teeth TongXin switch can

The principle of operation

Flow switch is the presence or absence of flow through the output switch control signal to the water sensor switch, the main switch signal. Divided into specific types normally open and normally closed type, in the main water control work flow monitoring role to play. Water flow switch and relay use with the usual components of the water control system, easy to use, no power is the flow switch on.

Electrical characteristic

Switch parameters	temperature range 70W	Unit	Features
maximum voltage	DC220/AC250	V	Switch for the imported dry reed pipe
breakdown voltage	DC400	V	Small flow start, big flow work
Max current	1	A	Start flow rate can be adjusted
load current	1.5	Max A	No standby power consumption
contact resistance	0.2	MaxΩ	One-way control, prevent backwater
Insulation Resistance	10 ⁸	MinΩ	Industrial control and water treatment of good assistant
temperature range	-40--120	°C	Other specifications and wiring length can be made to order
NOTE:			
1、 When magnetic materials or to flow switch a magnetic force materials near water flow switch, its characteristics may change.			
2、 In order to avoid particles, sundry into the flow switch, in the inlet must install screen pack.			
3、 In the use of the water flow switch before please read the parameters that if there are still questions please to our factory technical personnel consultation.			
4、 In the process of installation and use must cooperate relays (power in 3 W below), lest because of switch power small and dry reed pipe burn out.			
5、 The water flow switch installation use environment to avoid strong vibration and shaking place, in order to avoid water flow switch produce false action.			

Installation instructions

1, flow switch installation environment to avoid strong vibration, and shaking with the local magnetic environment, in order to avoid the flow switch malfunction. In order to avoid particles, debris into the water flow switch must be installed in the inlet filter.

2, when the magnetic material close to the water flow switch, its characteristics may change.

3, flow switches, relays must be compatible with use, as less power reed switch (typically 10W and 70W) easy to burn. Relay maximum power 3W, 3W power will be greater than the normally open and normally closed phenomenon.



Shenzhen OKD Technology Co.,Ltd.

Add:Room 2009 Dingcheng international building
Zhonghang Road Futian District Shenzhen
Tel:86-755-83661511
Fax:86-755-83559755
Email:szsokd@sina.com
Site:http://www.sz-okd.com
QQ:137030453